

VOYGAR 1U, Modular, STP, Patch Panel 24 Port Empty

Ref: PEMP1S4S



Product Overview

VOYGAR modular unloaded panel with rear cable management. 24 port 1U with labelling field. Double skin powder coated steel design allows snap in RJ45 connectors to fit flush to the front panel for a professional appearance.

Features

- Integral, removable cable management
- Data, Voice, video and other applications
- Clear numbering on the front of each RJ45 port
- Earth bonding point and 400mm earth wire provided

General Specifications

| | |
|-----------------------|----------------------------------|
| Support Bar Material | SPCC, Electrophoretic deposition |
| Support Bar thickness | 1.5mm |
| Rear Panel Material | SPCC |
| Rear Panel Thickness | 1.5mm |
| Panel Back | SPCC |
| Panel Back thickness | 1.5mm |
| Frame | Poly Stickers |
| Window | PS |
| Cable Type | U/FTP, F/UTP, F/FTP, S/FTP |
| Rack Type | EIA 19 inch |
| Rack Units | 1 |
| Total Ports Quantity | 24 |
| Product Type | Panel Modular |
| Form Factor | Flat |
| Package Quantity | 1 |

Technical Specs

| | |
|---------------------|--------------------|
| Interface Type | RJ45, Keystone |
| Shield Type | STP |
| Category acceptance | CAT5E, CAT6, CAT6A |

Dimensions

| | |
|--------|---------|
| Height | 44mm |
| Width | 482.6mm |
| Depth | 134mm |

Environmental Specifications

| | |
|------------------------|---------------------------|
| Flammability Rating: | UL 94 V-0 |
| Relative Humidity: | Up to 95%, Non-Condensing |
| Operating Temperature: | -10 °C to +60 |
| Storage Temperature: | -40 °C to +70 |

Standard

- ISO/IEC 11801
- ISO/IEC 11801
- IEC 60603-7
- FCC part 68-F
- RoHS
- UL