

VOYGAR Fibre Patch Cord, Multimode OM3, LC/LC, duplex.

Features

Telecommunications
Data centres
Test and measurement
10/100/1000 E
10 GE



Construction Materials

Fibre Type	MM OM3
Cable Type	Duplex
Fibre's quantity	2
Cable Length	1/3/5/10M
Construction Type	Patch cord
Connector A	LC Duplex
Connector B	LC Duplex
Polish	UPC
Ferrule	Ceramic
Diameter on Sheath	900nm
Cladding Diameter	125nm
Mode Field Diameter	50nm

General Specifications

Cable Sheath Colour	Aqua
Colour, connector A	Grey
Insertion Loss	≤0.2dB
Return Loss	≥50dB
Tensile Strength	100 N

Environmental Specifications

Environmental Space	LSZH
Operating Temperature	-10 °C to +75 °C

Standards

RoHS 2011/65/EU
ISO 9001:2008
IEC 60332-1-1
IEC 61300-3-4

Ordering Information

M322DX01	Fiber Patch Cord, Multimode OM3, LC/LC, duplex, 1M
M322DX03	Fiber Patch Cord, Multimode OM3, LC/LC, duplex, 3M
M322DX05	Fiber Patch Cord, Multimode OM3, LC/LC, duplex, 5M
M322DX10	Fiber Patch Cord, Multimode OM3, LC/LC, duplex, 10M